

# ECLIPSE

Analog Solid State UHF Transmitter  
5kW to 40kW and beyond



**ECLIPSE 10kW**

## ECLIPSE: Performance that Stands in Front of All Others

*Take Notice. Magnum inspired. Performance renowned.* Eclipse Series is a rugged and reliable Universal Analog UHF Solution for broadcast standards worldwide.

LARCAN's Eclipse Series captures progress and defines possibility - delivering unsurpassed performance through state-of-the-art technology. Integrating the award winning innovations of our Magnum Series of digital transmitters, Eclipse takes technical innovation to new levels for analog.

Eclipse. The Dawn of a New World Standard of Performance – Choose 5kW to 40kW and beyond!

- 100% Solid State Analog UHF Transmitter
- Broadband Amplifier (No tuning Adjustments)
- Customizable Cooling System
- Extensive Monitoring and Diagnostics
- Cost Effective, High Performance
- Reliable and User Friendly
- Fully Regulated Power Supplies
- Future Digital Capability

# ECLIPSE

Analog Solid State UHF Transmitter

## ECLIPSE – Take Notice. An Innovative Universal Analog Solution

Designed for broadcast standards worldwide, Eclipse is the outcome of engineering at its best. A solid and superior analog design – Eclipse is the best fit for broadcasters who want the ultimate in performance.

Developed from 'start to success' with the same renowned LARCAN quality of past generations – the Eclipse melds together proven technology with rugged performance and rich delivery.

Innovative features include our broadband LDMOS amplifiers, which require no tuning and offer the reliability you've come to expect from LARCAN - every time.

Looking for a Better Fit?  
*We hear you. Loud and clear.*



### ECLIPSE 10kW Specifications

#### CCIR System G / K Transmitter

Output	Power	10kW Vision / 1kW Sound		
	Frequency	470-860 MHz		
	Output Connector	3 1/8" EIA Unflanged		
Input	Input Impedance	75 ohms, unbalanced		
	Input Level	0.2 to 2.0 V p-p		
Performance	System G		System K	
	-4.43 MHz	-42 dB	-4.43 MHz	-42 dB
	-1.25 MHz and lower	-24 dB	-1.25 MHz and lower	-24 dB
	Carrier to -0.5 MHz	±0.5 dB	Carrier to -0.5 MHz	±0.5 dB
	Carrier to +200 kHz	0 dB (ref)	+1.5 MHz	0 dB (ref)
	Carrier to +5.0 MHz	±0.5 dB	Carrier to +5.8 MHz	±0.5 dB
	5.0 MHz to 7.0 MHz	-30 dB	6.5 MHz to 8.0 MHz	-30 dB
	Frequency Stability	±150 Hz		
	Harmonic Radiation	-80 dB		
Vision	Differential Phase	±3°		
	Differential Gain	±5%		
	Variation with Brightness	±0.6 dB		
	2T Pulse Response	1%		
	ICPM	±3°		
	Video Noise	-55 dB		
Sound	FM Noise	-62 dB		
	AM Noise	-60 dB		
	Distortion	0.5%		
	Response	±0.5 dB		
General	Power Requirements	55kW (est.) Black Picture		
	Voltage	208/380/415 VAC		
	Temp Range	0 to 40° C		
Dimensions	Height	1993.9 (mm)		
	Width	1244.6 (mm)		
	Depth	1117.6 (mm)		

The Eclipse Series PA Module design combines the expertise and experience of our legendary M Series transmitters with an innovative new stripline coupler design (patent pending). The result is innovation – unprecedented levels of power density and superior linearity.

