

MX^D SERIES

The evolution of 40+ years of experience

SIMPLICITY • RELIABILITY • MODULARITY • SERVICEABILITY

MXD 10U

10 Watt Digital UHF Transmitter / Translator



***FCC Certified**

Frequency Agile

**8VSB ATSC Modulator
(with Upconverter) or
Transcoder / REGEN**

Broadband Amplifier

**Adjacent Channel
Operation Capable**

**Linear, Regulated
Power Supply**

Channel Mask Filter

LARCAN

LARCAN USA • 1390 Overlook Drive • Lafayette, CO 80026

www.larcan.com Phone: (303)665-8000 • Fax: (303)673-9900 • Email: sales@larcan.com

MX^D SERIES

The evolution of 40+ years of experience

SIMPLICITY • RELIABILITY • MODULARITY • SERVICEABILITY

MXD 10U - FCC Certification No.:
BZ5MXD10U

MXD 10U SPECIFICATIONS

THE **MXD Series** IS THE NEW STANDARD IN BROADCAST TRANSMITTERS. DESIGNED UPON THE PRINCIPLES OF

- SIMPLICITY
- RELIABILITY
- MODULARITY
- SERVICEABILITY

THEY ARE BUILT TO LAST. PERIOD.

BROADBAND DESIGN

WITH STATE-OF-THE-ART BROADBAND AMPLIFIERS.

LINEAR, REGULATED POWER SUPPLY

RESPONSIBLE FOR PROVIDING DEPENDABLE, UNINTERRUPTED SERVICE WITH MINIMAL MAINTENANCE REQUIREMENTS AND MAXIMUM SURGE PROTECTION - TO KEEP YOU ON THE AIR.

FIELD TESTED FOR DIGITAL

THE AMPLIFIERS COME FROM THE LARCAN FIELD-TESTED GENERATION OF DTV TRANSMITTERS, WHICH MAKES THE **MXD Series** THE EQUIPMENT OF CHOICE FOR THE FUTURE.

Due to continuous product improvements, specifications subject to change without notice.

©2010 LARCAN

Transmitter - ATSC

Output	Power	10W
	Frequency	470-806 MHz
	Output Connector	N-Type
	Out-of-Band Emissions	FCC mask
	Signal-to-Noise	27dB
	Pilot Phase Noise	-101 dBc/Hz (20kHz offset)
	Pilot Carrier Frequency Stability	10kHz

Input	Interface	SMPTE310M
	Bit Rate	19.39 MB/s
	Symbol Clock Frequency	10.762238 MHz
	Impedance	75 Ohms

General	Power Requirements	500 Watts
	Voltage	107-120VAC single phase
	Dimensions (inches)	h w d 7 19 18
	Temperature Range	0 to 45 C
	Humidity	95%

Translator - ATSC

Output	Power	10W
	Frequency	470-806 MHz
	Output Connector	N-Type
	Out-of-Band Emissions	FCC mask
	Signal-to-Noise	27dB
	Pilot Phase Noise	-101 dBc/Hz (20kHz offset)
	Pilot Carrier Frequency Stability	10kHz

Input	Frequency Range	54-806MHz
	Connector	F-Type
	Input Level	-78 to -8 dBm/6MHz
	Impedance	75 Ohms

General	Power Requirements	500 Watts
	Voltage	107-120 VAC single phase
	Dimensions (inches)	h w d 7 19 18
	Temperature Range	0 to 45 C
	Humidity	95%

*NOTE: For more detailed translator specifications, please refer to the 8VSB REGEN Transcoder Datasheet.

